



Specialty Paints & Products for
Sign · Branding · Re-Imaging
1.800.421.7961

Q-MASK™ BM4100™ BOOTH MASKING

Q-MASK™ BM4100™ is a water-based, white strippable masking used to increase spray booth cleanliness and light reflectivity. **Q-MASK™ BM4100™** is a combination of emulsified resins, plasticizers and distilled water. **Q-MASK™ BM4100™** is 0% VOC and is low in HAPS - hazardous air pollutants.

QH&F Environmentally Friendly Product.

APPLICATION:

1.



Safety:

Use only NIOSH approved respirators and personal protection.

Always read the MSDS – Material Safety Data Sheets for safety warnings prior to use.

2.



Storage:

Product must be kept from freezing.


3.



Surface Cleaning:

Remove any existing surface contaminants.

4.



Q-MASK™ BM4100™ is ready to spray with no reduction required.

5.



Spray Gun Recommendations:

Airless: .017-.023”mm
Siphon Feed: 2.2 mm” or larger

6.



Spray Application:

Spray apply approximately 20 wet mils minimum.
Utilize a wet film thickness gauge.

7.



Dry Time:

Dry at 75°F-95°F @ 50% R.H. in 12 -24 hours.
Increasing air-flow (fans) speeds up dry time.
Do not force dry **Q-MASK™ BM4100™** with heat.

Always test surface preparation, primer and topcoat compatibility to determine acceptability before any production run.

Disclaimer: Technical information and suggested uses are believed to be reliable by QH&F Ltd., but such information or suggestions do not constitute a warranty. QH&F Ltd. has no control over the conditions under which the product is stored, handled, used or applied. Buyers must determine for themselves the suitability of each product for their specific use.