



Specialty Paints & Products for
Sign · Branding · Re-Imaging
1.800.421.7961

Q-SOLV™ UR™ SERIES URETHANE REDUCERS

Q-SOLV™ UR™ Series Reducers are specifically designed to reduce **Q-COAT UC™** Urethane Coatings to provide the best spray application properties. Temperature, relative humidity, air movement, and application surface size all play a major role to be successful in painting any surface. Selection of the Reducer is the key for best results.


QHF **Environmentally Friendly** Product.

RECOMMENDED REDUCER APPLICATIONS WITH Q-COAT UC™ URETHANE COATINGS:

Aluminum, Fiberglass, steel and many existing paint finishes. Test compatibility prior to production runs.

Q-SOLV UR™ REDUCERS:

Q-SOLV™ UR1004™ Accelerated Reducer:	Use below 75°F on small / large surface areas
Q-SOLV™ UR1054™ Fast Reducer:	Use below 75°F on small / large surface areas
Q-SOLV™ UR1056™ Medium Reducer:	Use above 75°F on small / large surface areas
Q-SOLV™ UR1060™ Slow Reducer:	Use above 85°F on small / large surface areas
Q-SOLV™ UR1062™ Extra Slow Reducer:	Use above 85°F on small / large surface areas
Q-SOLV™ UR1091™ Leveling Additive:	Use only as needed
Q-SOLV™ UR1094™ Accelerator:	Accelerator and Pot Life Extender
Q-SOLV™ UR1099™ Accelerator:	Accelerator
Q-SOLV™ UR1154™ Low VOC Fast Reducer:	Use below 75°F on small / large surface areas
Q-SOLV™ UR1156™ Low VOC Med Reducer:	Use above 75°F on small / large surface areas
Q-SOLV™ UR1160™ Low VOC Slow Reducer:	Use above 85°F on small / large surface areas
Q-SOLV™ UR1162™ Low VOC Extra Slow Reducer:	Use above 85°F on small / large surface areas



Reduction Ratio:

4 parts **Q-COAT UC™** Coating Color
1 part **Q-ACTV™ UA5000™** Activator
1 part **Q-SOLV UR™** Series Reducer



Specialty Paints & Products for
Sign · Branding · Re-Imaging
1.800.421.7961

Q-SOLV™ UR™ SERIES URETHANE REDUCERS

Optional Additive:

Up to ½ oz Accelerator per mixed quart in high gloss level colors
Up to 1 oz Accelerator per mixed quart for lower gloss level colors

Always test surface preparation, primer and topcoat compatibility to determine acceptability before any production run.

Disclaimer: Technical information and suggested uses are believed to be reliable by QH&F Ltd., but such information or suggestions do not constitute a warranty. QH&F Ltd. has no control over the conditions under which the product is stored, handled, used or applied. Buyers must determine for themselves the suitability of each product for their specific use.

® is a registered trademark and ™ is a trademark of Quill Hair & Ferrule LTD. Copyright © 2009. Quill Hair and Ferrule LTD. All Rights Reserved.